

Symbols

<!DOCTYPE> declaration 79, 110
\$db variable 105
\$(document).ready function 256, 263

Numerics

3D drawing
 complex models for 301
 overview 297–298

A

abort() method 319, 332–333
about:flags page 395
accessibility 9–10
Accessible Rich Internet Applications. *See* ARIA
accuracy attribute 327
action, forms 52
activeCues array 401
addElement() method 321
addEventListener() method 86, 100, 102–103, 126
agile planning board example
 building process for 114–115
 business logic for 119–123
 handling updates in browser 123
 handling updates on server 124–125
 overview 113–114
 prerequisites for 114
 template page 118–119
Airplane Mode 161
Aliens game
 collision detection 224
 CSS file for 205–206
 defense shields 221–222
 game engine base 214–215
 Game Over screen 211
 heads-up display 225–227
 html page for 204
 keyboard controls 219–221
 lasers 223
 mouse controls 219–221
 overview 202–204
 player ship 218
 screen transitions 215–216
 Start screen 210–211
 UFOs
 animating 229
 creating big UFO 217–218
 dynamic movement of 230–231
 flocks of 227
 making UFOs shoot 232
 paths for 228
altitude attribute 327
altitudeAccuracy attribute 327
<animate> tag 202, 206, 208
animation
 Canvas Ricochet game 173
 for SVG 208
 UFOs in SVG Aliens game 229
Apache web server 347–350
API method 19, 26, 140–141
.appcache extension 158
app.js file 59, 73, 365–368, 370–371
application cache manifest file 132
 configuring MIME types for 157–158
 creating 158–160
 detecting changes in 160–162
arc() method 178
arcTo() method 179

ARIA (Accessible Rich Internet Applications) 4, 9–10

arrays 283

<aside> elements 8–9

attributes

- data-* attributes 46–47
- for form elements 12–13
- for input types 41–43
- max attribute 46
- min attribute 46
- pattern attribute 49–50
- required attribute 44

audio

- Audio API 21–22, 313
- <audio> element 22, 242
- browser compatibility 239
- converting between formats 252
- custom controls for 255–256
- Firefox browser 248
- Media Element interface
 - events in 245–246
 - overview 244
 - properties of 245
- multiple formats with <source> element
 - browser compatibility 248
 - discovering which video is playing 249–251
- Opera browser 248
- prerequisites for 239–240
- reference links for 427
- telestrator jukebox application
 - adding <canvas> element 253–254
 - adding clear button 264
 - adding frame around video 257–260
 - adjusting video opacity 260
 - capturing mouse movement 263
 - custom playback controls 255–256
 - determining state of media
 - resources 245
 - displaying captured path over video 263
 - grayscale video 261–262
 - layout for 240–241
 - loading list of videos 243
 - overview 238–240
 - playing video on canplaythrough event 246
 - starting video when selected 244
 - switching between videos 244
 - using event handlers to change video 245
 - <video> element 241–242
- auto-complete, using cross-document messaging 127–129
- autofocus attribute 41, 43
- autoplay attribute 324

B

background

- Canvas Ricochet game 174–175
- Full-Screen API 414

ball, Canvas Ricochet game

- creating 178–179
- moving 182

Ball.collide() method 184

Ball.draw() method 194

Ball.move() method 182

Battery API 418–420

bitmap graphics vs. SVG 200–202

bounding box 231

Brick.draw() method 191

bricks, Canvas Ricochet game

- coloring 177–178
- creating 175
- removing hit bricks 184–185

Bricks.collide() method 191

browsers

- compatibility
 - Canvas API 169–170
 - using <source> element 248
 - video 239
- development versions 379–380
- for Geometry Destroyer game 270–271
- WebSocket protocol support 362–363

buffered attribute 324

buffers

- for color 287–288
- for dimension 287–288
- displaying shape data using 288
- for shape 287–288

build() method 216–217

bullets, Geometry Destroyer game 299–300

business logic 119–123

bypassing form validation 51

C

CACHE section 158–160

cached event 318

calculations in forms

- data-* attributes 46–47
- functions to calculate total values 53–54
- min and max attributes 46
- number input type 46
- <output> element 47, 57
- retrieving price values 56–57
- retrieving value of input fields 55
- valueAsNumber property 54

canplay event 245

canplaythrough event 245–246

canPlayType() method 324

- Canvas API
 - Canvas Ricochet game
 - animation for 173
 - background image 174–175
 - coloring bricks 177–178
 - creating ball 178–179
 - creating game bricks 175
 - creating paddle 179
 - enabling collision detection 184
 - enabling edge detection 183
 - engine object for 171–173
 - Game Over screen for 194–195
 - keyboard controls for 186, 188–189
 - making ball move 182
 - mouse control for 187
 - moving paddle 182
 - removing hit bricks 184–185
 - score counter for 190–191
 - storing high scores online 192
 - testing 180
 - touch support for 187
 - Welcome screen for 193–194
 - contents of canvas element 169
 - libraries for ImpactJS 195
 - overview 21, 165–166, 313
 - reference links for 426
 - setting context 166–169
 - vs. SVG
 - community support 232–233
 - documentation 232–233
 - JavaScript integration 233
 - pros and cons of 233–234
 - verifying browser support 169–170
- <canvas> element 20–21, 32, 168–169, 234, 253–254
- CanvasRenderingContext2D interface 168
- card_cv2 field 49
- card_number field 49
- Cascading Style Sheets. *See* CSS
- channel messaging 129
 - adding JavaScript to first page 375
 - adding JavaScript to second page 376–377
 - creating example pages 375
 - cross-domain test environment 373–374
 - installing local development web server 374
- chargingchange 419
- chargingTime 418
- chargingtimechange 419
- chat application example
 - chat form 105–106
 - connecting to stream in browser 111
 - creating database 105
 - creating server stream 109–111
 - implementing login process 107–108
 - login form 106–107
 - overview 102–105
 - sending chat messages to server 108
 - storing messages in database 108–109
- chat.js file 109, 127
- chat.sql file 344
- checkEnclosure() method 230
- checking event 318
- checkIntersection() method 230
- checkValidity() method 60, 66, 318
- Chrome developer tools 379
- class attribute 135–137, 140
- clear() method 130, 323
- clearData() method 322
- clearWatch() method 326
- client-side validation 13
- cmp() method 328
- codecs, discovering which used in video 386
- collapsible content 14–15
- collide() method 184, 217
- collision detection
 - displaying shape data 290
 - Geometry Destroyer game 303
 - for items in canvas 184
 - SVG Aliens game 224
- color buffers 287–288
- combobox example 9
- Command+Shift+H keyboard shortcut 350
- community support
 - for Canvas 232–233
 - for SVG 232–233
- Configuration page, MySQL installer 342
- Constraint Validation API 317
 - See also* validating forms
- contact details section, order form
 - example 43
- contenteditable attribute 25, 79, 81
- context, setting for canvas 166–169
- continue() method 328
- controller attribute 324
- controls attribute 242, 324
- controls, video playback 255–256
- converting video formats 252
- coords attribute 327
- core.js file 279
- CORS (Cross Origin Resource Sharing) 324
- cp.core.draw() method 290
- Create File zone 97
- createEmptyItem() function 148
- createFormSubmit() method 91, 93
- createIndex() method 130, 146, 330
- createObjectStore() method 130, 146, 329
- createReader() method 334
- createWriter() method 333
- Cross Origin Resource Sharing. *See* CORS

- cross-document messaging 102
 - auto-complete using 127–129
 - overview 24, 125–126
 - using postMessage method 126–127
- cross-domain environment 373–374
- cross-domain messaging 125, 127
- crossOrigin attribute 324
- CSS (Cascading Style Sheets) 10
 - controlling visibility of views using 137
 - and HTML5 18
 - overview 314
 - pseudo-classes 61–62
- Ctrl+Shift+_ keyboard shortcut 349
- Ctrl.init() method 186–187
- ctx.beginPath() method 179
- ctx.closePath() method 179
- cube particles, Geometry Destroyer game
 - creating 305
 - customizing 306–307
- cube() method 302
- cuechange event 404
- currentSrc attribute 249–251, 324
- currentTime attribute 255, 324
- cursors 130, 150
- customError attribute 318

D

- data-* attributes 45–47
- dataset property 56
- Date object 54
- defaultMuted attribute 325
- defaultPlaybackRate attribute 256, 325
- defense shields, SVG Aliens game 221–222
- delete_worker() method 122
- delete() method 154–155, 328
- deleteDatabase() method 130, 155–156, 328
- deleteTask() function 154
- designMode property 25, 76, 78–81
- <details> element 15, 74
- Developer Default option 341
- Device Orientation API
 - locking orientation 417
 - overview 415–417
- dimension buffers 287–288
- direction attribute 328
- DirectoryReader object 88
- dischargingTime 419
- dischargingtimechange 419
- displayBrowserFileList() function 88, 98
- displayFileSystem() function 88–89
- <div> elements 6–7, 10
- document.execCommand() method 26
- document.getElementById() method 57
- document.getItems() method 323

- DOM (Document Object Model)
 - and HTML5 19–20
 - pulling shader data from 285–286
- downloading event 318
- Drag and Drop API 70, 96–97
 - exporting files using 98–99
 - importing files using 97–98
 - overview 22–23
 - reference for 321–322
- drag event 322
- dragend event 322
- dragenter event 322
- dragFile() function 98
- draggable attribute 23, 70
- dragleave event 322
- Dragonfly 379
- dragover event 97–98, 322
- dragstart event 70, 98, 322
- draw_welcome() function 408
- draw() function 254, 260–261, 263–264, 419
- drop event 322
- dropDatabase() function 155–156, 160
- dropEffect() method 321
- duration attribute 255, 325
- dynamic content, serving with Node.js
 - creating static template with placeholders 367
 - mixing dynamic content into template 368
 - testing in browser 368–369

E

- edge detection 183
- edges() method 183
- Editing API 320
- effectAllowed() method 321
- element.dataset.personName 56
- email input type 41–43, 67
- enableHighAccuracy attribute 326
- encoding video with FFmpeg
 - to MP4/h264 with AAC 387–388
 - to MP4/h264 with MP3 388
 - to Ogg/Theora 389
 - to WebM/VP8 388–389
- ended attribute 325
- enemy, Geometry Destroyer game
 - collision detection for 303
 - creating 304–305
 - generating random properties for 302
 - overview 300
- engine, custom WebGL
 - base engine logic 277
 - browser support for example 270–271
 - entity helper methods 280–281
 - entity storage 278
 - index.html 271–272

engine, custom WebGL (*continued*)
 overview 269–270
 requestAnimationFrame() function 275
 shape entities with 3D data 279
 Simple JavaScript Inheritance script 275
 style.css 273
 sylvester.js 276
 time-saving scripts for 274–275
 webgl_util.js 276
 error attribute 325
 error event 319, 332–333
 event-driven applications
 vs. polling 357–360
 server-side choices for 360
 EventEmitter.js 114, 119–120
 events
 changing videos using 245
 Media Element interface 245–246
 Text Track API 404–405
 EventSource interface 25, 102, 111
 execCommand() method 70, 78, 81, 320
 exiting full-screen mode 415
 Expiry Date field 65
 exporting files using Drag and Drop API 98–99
 eXtensible Messaging and Presence Protocol. *See*
 XMPP

F

failure of form validation
 detecting with invalid event 60–61
 styling invalid elements 61–62
 FALLBACK section 159
 fallbackValidation() function 68
 favicon.ico 368
 FFmpeg tool
 determining supported codecs 387
 discovering codecs used on video 386
 encoding with
 to MP4/h264 with AAC 387–388
 to MP4/h264 with MP3 388
 to Ogg/Theora 389
 to WebM/VP8 388–389
 obtaining 386
 File API 30–31
 File Browser view 72–73, 92, 97
 File Editor view 72–73, 77–78, 86, 91, 94
 File Reader API 30–31
 File System API 70, 72–73
 creating files 90–91
 creating persistent filesystem 86–87
 deleting files 90–91
 getting list of files 87–89
 importing files from computer 92–94
 loading files in editor 89–90
 overview 30–31
 reference for 331–335
 saving files 94–96
 viewing files 90–91
 File Writer API 30–31, 94–96
 FileSaver() method 333
 fileSystem field 86
 Firebug 379
 Firefox browser 248, 270–271
 FLV (Flash video) format 21
 follow_mouse() function 412, 416, 423
 forever-frame hack 105
 <form> element 41
 formaction attribute 36, 38, 51–52
 formats, video
 browser compatibility using multiple 248
 converting between 252
 discovering which is being played 249–251
 formnovalidate attribute 36, 38, 51
 forms
 action for 52
 fallbacks for unsupported browsers
 detecting features with Modernizr 63–64
 month-picker fallback 64–65
 validating form without constraint validation
 API 65–68
 input types
 attributes for 41–43
 email input type 41–43
 month input type 49
 pattern attribute 49–50
 required attribute for 44
 tel input type 41–43
 new features
 client-side validation 13
 new form attributes 12–13
 new form input types 11
 order form example
 basic document structure 40–41
 contact details section 43
 login details section 44
 order details section 47
 overview 38–39
 payment details section 50
 prerequisites for 39–40
 performing calculations in
 data-* attributes 46–47
 functions to calculate total values 53–54
 min and max attributes 46
 number input type 46
 <output> element 47, 57
 retrieving price values 56–57
 retrieving value of input fields 55
 valueAsNumber property 54
 reference links for 425

- forms (*continued*)
 - validating
 - bypassing to save form details 51
 - custom validation 59–60
 - detecting failure with invalid event 60–61
 - styling invalid elements 61–62
 - fragment shader 283
 - frame around video 257–260
 - framebuffer 283
 - fs.readFile() method 366
 - Full-Screen API
 - entering full-screen mode 414
 - exiting full-screen mode 415
 - styling background 414
 - future HTML developments
 - Battery API 418–420
 - Device Orientation API
 - locking orientation 417
 - overview 415–417
 - Full-Screen API
 - entering full-screen mode 414
 - exiting full-screen mode 415
 - styling background 414
 - Mouse Event Capture API 411–413
 - Pointer Lock API 420–423
 - real-time media access and communication
 - getUserMedia() function 391–393
 - overview 390–391
 - WebRTC specification 394
 - test bed for exploring 406–411
 - Text Track API
 - adding multiple track elements 397–400
 - adding track element 396–397
 - checking to see if track is loaded 403–404
 - events for 404–405
 - loading text tracks in advance 403
 - styling for 405–406
 - Vibration API 417–418
- G**
-
- Game Over screen
 - for Canvas Ricochet game 194–195
 - for SVG Aliens game 211
 - Game.draw() method 190
 - Game.init() method 190, 193
 - game.js file 280
 - Game.levelLimit() method 191
 - Game.levelUp() method 191
 - Game.restartGame() method 195
 - Game.runGame() method 193
 - Game.setup() method 173, 186
 - gd.core.animate() method 305
 - gd.core.draw() method 288
 - gd.core.shader.get() method 286
 - gd.core.shader.init() method 286
 - gd.core.shader.store() method 286
 - gd.gl.vertexAttribPointer() method 289
 - gd.template.Cube.init() method 306
 - gd.template.Entity.color() method 287
 - gd.template.Entity.indices() method 287
 - gd.template.Entity.shape() method 287
 - gd.template.Polygon 301–304
 - Geolocation API
 - inserting map of user location 83–84
 - overview 29, 82–83, 315
 - reference for 326–327
 - Geometry Destroyer game
 - 3D cube particle 305
 - 3D Polygon enemy 300
 - animating player entity 298
 - capturing user input 294
 - collision detection for enemies 303
 - creating enemies 304–305
 - creating player entity 296
 - customizing cubes 306–307
 - generating random enemy properties 302
 - HUD 295
 - player bullets 299–300
 - square particles 308
 - get_task() method 122
 - getAsFile() method 322
 - getAsString() method 322
 - getAttribute() method 56
 - getAttributeNS() method 213
 - getBoundingBox() method 231
 - getBlob() method 335
 - getContext() method 381
 - getCueAsHTML() method 402
 - getCurrentPosition() method 70, 82, 326
 - getData() method 322
 - getDirectory() method 334
 - getEnclosureList() method 230
 - getFile() method 89–90, 334
 - getImageData() method 261–262
 - getIntersectionList() method 230
 - getItem() method 130, 140, 323
 - getUserMedia() method 391–393
 - Global Positioning System. *See* GPS
 - globalAlpha property 260
 - globalCompositeOperation property 258
 - go() function 407–408, 410, 414, 420, 422
 - Google Chrome 270–271
 - GPS (Global Positioning System) 326
 - gradient() method 177
 - graphics cards 283–284
 - grayscale video 261–262

H

HAVE_CURRENT_DATA property 246
 HAVE_ENOUGH_DATA property 246
 HAVE_FUTURE_DATA property 246
 HAVE_METADATA property 246
 HAVE_NOTHING property 246
 headers, HTTP 355–357
 heading attribute 327
 heads-up display. *See* HUD
 height attribute 242
 Hello World application using Node.js 365–366
 history of HTML5 310–311
 home page, MySQL Workbench 344
 hp (hit points) 221
 .htaccess file 157
 <html> element 5, 382
 HTML5 (HyperText Markup Language 5)
 Audio and Video APIs 21–22
 Canvas API 21
 collapsible content without JavaScript 14–15
 cross-document messaging 24
 and CSS3 18
 and DOM 19–20
 Drag and Drop API 22–23
 enhancing accessibility using ARIA
 roles 9–10
 File API 30–31
 File Reader API 30–31
 File System API 30–31
 File Writer API 30–31
 forms
 client-side validation 13
 new form attributes 12–13
 new form input types 11
 Geolocation API 29
 history of 310–311
 IndexedDB API 29–30
 Internet Explorer support
 overview 10
 printing new elements properly 11
 rendering new elements properly 10
 and JavaScript 19–20
 meters 14
 microdata 16–18
 offline web applications 27–28
 progress bars 14
 rich-text editing of documents 25–26
 semantic elements in 6–9
 server-sent events 25
 specifications for 316
 structure of documents 5–6
 SVG 31
 technologies not officially part of 312

tools for
 browser development versions 379–380
 Chrome developer tools 379
 Dragonfly 379
 Firebug 379
 HTML5 Boilerplate 382
 HTML5 Shiv 379–380
 IE developer tools 379
 jsFiddle 383–384
 Modernizr 380–382
 Safari developer tools 379
 Web Storage API 25–27
 WebGL 32
 WHATWG vs. W3C 311–312
See also future HTML developments
 HTML5 Boilerplate 382
 HTML5 Shiv 379–380
 HTTP headers 355–357
 httpd.conf file 347–348, 350
 httpd.userdir.conf file 350
 HUD (heads-up display) 190
 Geometry Destroyer game 295
 SVG Aliens game 225–227
 Hud.update.level() method 227
 HyperText Markup Language 5. *See* HTML5

I

IDBOpenDBRequest interface 330
 IDE (integrated development environment) 379
 IETF (Internet Engineering Task Force) 360
 if statement 169
 ImpactJS library 195
 importing files
 using Drag and Drop API 97–98
 using File System API 92–94
 with XLink 209
 IndexedDB API 132
 adding data to 152–154
 connecting to 145–148
 deleting data 154–155
 detecting support for 144–145
 dropping database 155–156
 overview 29–30
 reference for 327–330
 searching 150–152
 updating data 154–155
 index.php file 106–107
 init() method 182, 216–217, 276, 280, 299, 306
 innerHTML property 57
 input types
 attributes for 41–43
 email input type 41–43
 month input type 49
 number input type 46

input types (*continued*)
 pattern attribute 49–50
 required attribute for 44
 tel input type 41–43
 <input> element 36, 38, 40, 47, 59, 65, 331
 INSERT statement 153
 insertImage() function 83
 insertTask() function 153
 integrated development environment. *See* IDE
 Internet Engineering Task Force. *See* IETF
 Internet Explorer
 developer tools 379
 supporting new elements in
 overview 10
 printing new elements properly 11
 rendering new elements properly 10
 invalid event 36, 58, 60–61
 IP (Internet Protocol) 355
 isDirty variable 80

J

JavaScript
 collapsible content without using 14–15
 and HTML5 19–20
 interaction with Canvas 233
 interaction with SVG
 vs. Canvas 233
 overview 212–214
 libraries 315–316
 navigating between views using 137–139
 JavaScript Object Notation. *See* JSON
 jQuery 315–316
 jsFiddle 383–384
 JSON (JavaScript Object Notation) 19

K

key attribute 328
 key() method 323
 keyboard controls
 Canvas Ricochet game 186, 188–189
 SVG Aliens game 219–221
 kind attribute 397, 399–401

L

lasers, SVG Aliens game 223
 Laser.update() method 224
 latency 357
 latitude attribute 327
 levelchange 419
 element 98, 249
 libraries, Canvas API
 ImpactJS 195

lineTo() method 179
 links
 for Canvas API 426
 for messaging 425–426
 for mobile applications 426
 for SVG 426
 for video and audio 427
 for WebGL 427
 list directory command. *See* ls command
 load event 332
 load() method 325
 loadeddata event 245
 loadedmetadata event 245
 loadend event 332
 loadFile() function 89–90
 loadSettings() function 140–141
 loadstart event 332
 loadTasks() function 146, 150–151
 localStorage
 deleting data from 141–143
 reading data from 140–141
 saving data to 141
 localStorage interface 27, 139–140
 location.hash property 133, 138
 locking orientation 417
 login details section, order form example 44
 longitude attribute 327
 loop attribute 325
 ls (list directory) command 347

M

Mac OS X
 MySQL
 configuring PHP for 352–353
 installing 351–352
 PHP
 configuring MySQL for 352–353
 editing Apache configuration files 347–350
 overview 345–346
 serving web files from sites directory 350–351
 using Terminal app 346–347
 makeGradient() method 177
 maps, user location on 83–84
 <mark> elements 8–9
 markAsComplete event 149, 154
 matrices 288
 max attribute 13, 45–46
 maximumAge attribute 327
 media
 adjusting opacity of 260
 browser compatibility 239
 converting between formats 252
 custom controls for 255–256
 and Firefox browser 248

- media (*continued*)
 - rayscale 261–262
 - Media Element API
 - events in 245–246
 - overview 244
 - properties of 245
 - multiple formats with <source> element
 - browser compatibility 248
 - discovering which video is playing 249–251
 - and Opera browser 248
 - prerequisites for 239–240
 - telestrator jukebox application
 - adding <canvas> element 253–254
 - adding clear button 264
 - adding frame around video 257–260
 - adjusting video opacity 260
 - capturing mouse movement 263
 - custom playback controls 255–256
 - determining state of media resources 245
 - displaying captured path over video 263
 - grayscale video 261–262
 - layout for 240–241
 - loading list of videos 243
 - overview 238–240
 - playing video on canplaythrough event 246
 - starting video when selected 244
 - switching between videos 244
 - using event handlers to change video 245
 - <video> element 241–242
- Media Element API
 - events in 245–246
 - overview 244
 - properties of 245
 - reference for 324
- mediaGroup attribute 325
- <menu> element 399
- messaging
 - agile planning board example
 - building process for 114–115
 - business logic for 119–123
 - handling updates in browser 123
 - handling updates on server 124–125
 - overview 113–114
 - prerequisites for 114
 - template page 118–119
 - chat application example
 - chat form 105–106
 - connecting to stream in browser 111
 - creating database 105
 - creating server stream 109–111
 - implementing login process 107–108
 - login form 106–107
 - overview 102–105
 - sending chat messages to server 108
 - storing messages in database 108–109
 - cross-document messaging
 - auto-complete using 127–129
 - overview 125–126
 - using postMessage method 126–127
 - reference links for 426
 - server-sent events 112
 - WebSockets 115–117
- <meter> element 14
- meters 14–15
- microdata
 - API reference 323
 - overview 16–18
- Microsoft Internet Explorer. *See* Internet Explorer
- Microsoft Windows 7. *See* Windows 7
- MIME types 31, 157–158
- mime.types file 158
- min attribute 13, 45–46
- mobile applications
 - IndexedDB API
 - adding data to 152–154
 - connecting to 145–148
 - detecting support for 144–145
 - dropping database 155–156
 - searching 150–152
 - updating and deleting data 154–155
 - My Tasks application example
 - adding new tasks 153
 - controlling visibility of views using CSS 137
 - creating views with <section> elements 136
 - deleting tasks 154
 - document structure for 135
 - implementing navigation with
 - JavaScript 137–139
 - navigation bar 135
 - overview 134–135
 - searching task view list 152
 - task list view 148–149
 - updating tasks 154
 - offline applications
 - configuring MIME type on server 157–158
 - creating application cache manifest file 158–160
 - detecting changes in manifest file 160–162
 - reference links for 426
 - tools for 378
 - Web Storage API
 - deleting data from localStorage 141–143
 - reading data from localStorage 140–141
 - saving data to localStorage 141
- Modernizr 380–382
- month input type 49, 64–65
- monthpicker.js file 41, 64
- mouse controls
 - Canvas Ricochet game 187
 - SVG Aliens game 219–221

Mouse Event Capture API 411–413
 movePaddle() method 187
 moveTask message 124
 Mozilla Firefox. *See* Firefox browser
 MP4/h264 with AAC encoding 387–388
 MP4/h264 with MP3 encoding 388
 multiEntry flag 146
 multimedia 313
 multiple attribute 92
 muted attribute 325
 My Tasks application example 132–133, 161

- adding new tasks 153
- controlling visibility of views using CSS 137
- creating views with <section> elements 136
- deleting tasks 154
- document structure for 135
- implementing navigation with JavaScript 137–139
- navigation bar 135
- overview 134–135
- searching task view list 152
- task list view 148–149
- updating tasks 154

 MySQL

- on Mac OS X
 - configuring PHP for 352–353
 - installing 351–352
- on Windows 7
 - creating databases 343–346
 - downloading 340–341
 - installing 341–343
 - running scripts 343–346

 mysql.sock file 352

N

navigating between views using JavaScript 137–139
 NETWORK section 159
 NETWORK_EMPTY property 245
 NETWORK_IDLE property 246
 NETWORK_LOADING property 246
 NETWORK_NO_SOURCE property 246
 networking

- event-driven applications
 - vs. polling 357–360
 - server-side choices for 360
- HTTP headers 355–357
- latency 357
- overview 354–355
- throughput 357
- WebSocket protocol
 - browser support for 362–363
 - overview 361–362
 - vs. WebSocket API 360–361

 networkState attribute 245, 325

node_modules directory 370
 Node.js 102, 112–115, 117–118, 129

- creating socket using 115–117
- creating web apps with 370–372
- Hello World application using
 - creating 365
 - running 365–366
- overview 315
- requirements for 364–365
- routing with 369–370
- serving mixed static and dynamic content with
 - creating static template with placeholders 367
 - mixing dynamic content into template 368
 - testing in browser 368–369
- serving static files with
 - loading file from disk 366
 - running application 367
 - sending file to browser 367

 nouupdate event 318
 novalidate attribute 51
 number input type 45

- overview 46
- retrieving value of 55

O

objectStore() method 152, 154
 obsolete event 319
 offline applications

- API reference 318–319
- configuring MIME type on server 157–158
- creating application cache manifest file 158–160
- detecting changes in manifest file 160–162
- overview 27–28

 Ogg/Theora video format 251, 389
 oncuechange property 404
 onmessage event 116, 126, 128, 375–376
 onsuccess property 331
 onupgradeneeded event 330
 opacity of video 260
 Open Connection to Start Querying heading 344
 open() method 130
 openCursor() method 130, 150, 329–330
 OpenGL ES (Open Graphics Library for Embedded Systems) 32, 284
 Opera browser 248
 options object 146
 or operators 144
 order form example

- basic document structure 40–41
- contact details section 43
- login details section 44
- order details section 47

order form example (*continued*)
 overview 38–39
 payment details section 50
 prerequisites for 39–40
 orientationchange event 140
 <output> element 40, 47, 57

P

<p> tag 188
 paddle, Canvas Ricochet game
 creating 179
 moving 182
 Paddle.move() method 182–183
 parseFloat function 55
 paths
 drawing in SVG 209–210
 for UFOs in SVG Aliens game 228
 pattern attribute 13, 49–50
 patternMismatch attribute 318
 pause() method 256, 325
 paused attribute 325
 payment details section, order form example 49–50
 PDO database 109
 persistent filesystem 86–87
 PHP
 files 106–107
 on Mac OS X Mountain Lion
 configuring MySQL for 352–353
 editing Apache configuration files 347–350
 overview 345–346
 serving web files from sites directory 350–351
 using Terminal app 346–347
 on Windows 7
 configuring Windows 7 IIS 336–337
 confirming installation 339
 downloading 337
 installing 338–339
 placeholder attribute 13, 41, 43
 planner.get_words() method 128
 plan.on() method 123
 play() method 325
 playbackRate attribute 256, 325
 played attribute 325
 Pointer Lock API 420–423
 pointerlockchange 420
 pointerLockElement 420
 pointerlockerror 420
 polling vs. event-driven applications 357–360
 Polygon.collide() method 308
 postMessage() method 100, 126–127, 375

preload attribute 325
 primaryKey attribute 328
 printing new HTML5 elements correctly
 in IE 11
 progress bars 14
 progress event 318, 332–333
 pseudo-classes 61–62
 putImageData() method 261
 python command 134

Q

quantum entanglement 375
 queryCommandEnabled() method 320
 queryCommandIndeterm() method 320
 queryCommandState() method 70, 82, 320
 queryCommandSupported() method 320
 queryCommandValue() method 320
 queryUsageAndQuota() method 70
 Quota Management API 70, 85–87

R

randomMeta() method 302
 rangeOverflow attribute 318
 rangeUnderflow attribute 318
 RDBMS (relational database management system) 145
 readAsArrayBuffer() method 332
 readAsText() method 70, 89, 332
 readEntries() method 334
 readyState attribute 245–246, 325
 real-time media access and communication
 getUserMedia() function 391–393
 overview 390–391
 WebRTC specification 394
 reference links
 for Canvas API 426
 for forms 425
 for messaging 426
 for mobile applications 426
 for SVG 426
 for video and audio 427
 for WebGL 427
 relational database management system. *See*
 RDBMS
 releaseCapture() method 411
 remove() method 90
 removeItem() method 130, 141, 323
 removeRecursively() method 334
 requestAnimationFrame() method 173, 240, 274–275, 305, 407
 requestFullscreen() method 414
 requestPointerLock() method 420
 requestQuota() method 70, 266

required attribute 13, 41, 43–44, 65, 68
 resetSettings() function 155–156
 rich-text editing of documents 25–26, 81
 Ricochet game (Canvas)
 animation for 173
 background image 174–175
 coloring bricks 177–178
 creating ball 178–179
 creating game bricks 175
 creating paddle 179
 enabling collision detection 184
 enabling edge detection 183
 engine object for 171–173
 Game Over screen for 194–195
 keyboard controls for 186, 188–189
 making ball move 182
 mouse control for 187
 moving paddle 182
 removing hit bricks 184–185
 score counter for 190–191
 storing high scores online 192
 testing 180
 touch support for 187
 Welcome screen for 193–194
 rotation logic 291
 routing with Node.js 369–370
 run.js file 271, 278, 280–282

S

Safari developer tools 379
 Save Settings button 143
 saveBtn.addEventListener() method 53
 Scalable Vector Graphics. *See* SVG
 scores, game
 counter for 190–191
 storing online 192
 screen transitions 215–216
 Screen.gameover() method 194
 script contexts 125
 <script> element 19, 116, 375–376
 searching using IndexedDB API 150–152
 <section> element 136
 seek() method 333
 seekable attribute 325
 seeking attribute 326
 self.applicationCache() method 319
 semantic elements 4, 6–9
 server-sent events. *See* SSE
 session_id() method 107–108
 session_start() method 110
 sessionStorage interface 27, 139
 setCapture() method 411–412
 setCustomValidity() method 36, 59, 318
 setData() method 322

setDragImage() method 321
 setInterval() method 173, 305
 setItem() method 130, 323
 setTimeout() method 305
 setversion() method 329
 shaders
 creating via OpenGL ES 284
 pulling shader data from DOM 285–286
 shapes
 buffers for 287–288
 creating in SVG 206–208
 Ship object 219
 showTask() function 148–150
 showUI argument 81
 Simple JavaScript Inheritance script 275
 SimpleHTTPServer module 374
 source attribute 328
 <source> element 248
 speed attribute 327
 spinbox component 46
 SQL database 150, 156
 SQLite database 30
 src attribute 242, 244, 248, 250, 326
 srclang attribute 399, 401
 SSE (server-sent events) 25, 102–103, 129, 314, 360
 chat application example
 chat form 105–106
 connecting to stream in browser 111
 creating database 105
 creating server stream 109–111
 implementing login process 107–108
 login form 106–107
 overview 102–105
 sending chat messages to server 108
 storing messages in database 108–109
 when to use 112
 Start screen 210–211
 startDate attribute 326
 state management 76–78
 static files
 loading file from disk 366
 running application 367
 sending file to browser 367
 stepMismatch attribute 318
 Storage APIs 132, 314–315
 storageInfo field 86
 streams
 connecting to stream in browser 111
 creating server stream 109–111
 String.Replace() function 368
 <style> element 253
 style.css file 73, 205
 sudo (switch user and do) command 348
 <summary> element 15, 74

- Super HTML5 Editor example
 - designMode property 79–80
 - Drag and Drop API
 - exporting files using 98–99
 - importing files using 97–98
 - execCommand method 81
 - file browser view 74
 - file editor view 75–76
 - File System API
 - creating files 90–91
 - creating persistent filesystem 86–87
 - deleting files 90–91
 - getting list of files 87–89
 - importing files from computer 92–94
 - loading files in editor 89–90
 - saving files 94–96
 - viewing files 90–91
 - File Writer API 94–96
 - Geolocation API
 - inserting map of user location 83–84
 - overview 82–83
 - main document structure 74
 - navigating between views 76–78
 - overview 72–74
 - reference links for 425–426
 - rich-text editing toolbar 81
 - state management for 76–78
 - SuperEditor() function 77
 - SVG (Scalable Vector Graphics)
 - adding shapes 206–208
 - adding text 208
 - Aliens game
 - animating UFOs 229
 - big UFO 217–218
 - collision detection 224
 - CSS file for 205–206
 - defense shields 221–222
 - dynamic movement of UFOs 230–231
 - game engine base 214–215
 - Game Over screen 211
 - heads-up display 225–227
 - keyboard controls 219–221
 - lasers 223
 - making UFOs shoot 232
 - mouse controls 219–221
 - overview 202–204
 - player ship 218
 - screen transitions 215–216
 - Start screen 210–211
 - svg tags in html 204
 - UFO flocks 227
 - UFO paths 228
 - animation 208
 - API overview 313
 - vs. bitmap graphics 200–202
 - vs. Canvas
 - community support 232–233
 - documentation 232–233
 - JavaScript integration 233
 - pros and cons of 233–234
 - drawing with paths 209–210
 - importing files with XLink 209
 - JavaScript interaction with 212–214
 - overview 31, 199–200
 - reference links for 426
 - <svg> element 202–204, 207, 210, 212
 - viewBox parameter 211–212
 - Wilson smiley example 201–202
 - swapCache() method 130, 160, 318–319
 - switch user and do command. *See* sudo command
 - svlvester.js file 276
-
- T**
- TCP (Transmission Control Protocol) 355
 - tel input type 41–43
 - teletrator jukebox application
 - adding <canvas> element 253–254
 - adding clear button 264
 - adding frame around video 257–260
 - adjusting video opacity 260
 - capturing mouse movement 263
 - custom playback controls 255–256
 - determining state of media resources 245
 - displaying captured path over video 263
 - grayscale video 261–262
 - layout for 240–241
 - loading list of videos 243
 - overview 238–240
 - playing video on canplaythrough event 246
 - starting video when selected 244
 - switching between videos 244
 - using event handlers to change video 245
 - <video> element 241–242
 - template page, agile planning board
 - example 118–119
 - Terminal app 346–347
 - test bed for exploring future HTML
 - developments 406–411
 - text property 401, 403
 - Text Track API 395–396, 400–401
 - adding multiple track elements 397–400
 - adding track element 396–397
 - checking to see if track is loaded 403–404
 - events for 404–405
 - loading text tracks in advance 403
 - styling for 405–406
 - text, in SVG 208
 - text/event-stream type 109
 - <text> element 208

- <textarea> element 25
- throughput 357
- timeout attribute 326
- timestamp attribute 327
- title attribute 50
- tooLong attribute 318
- tools
 - for HTML5 applications
 - browser development versions 379–380
 - Chrome developer tools 379
 - Dragonfly 379
 - Firebug 379
 - HTML5 Boilerplate 382
 - HTML5 Shiv 379–380
 - IE developer tools 379
 - jsFiddle 383–384
 - Modernizr 380–382
 - Safari developer tools 379
 - for mobile web applications 378
- touch support 187
- toURL method 90–91, 99
- <track> element
 - adding 396–397
 - adding multiple 397–400
- transaction() method 329
- transcoder 252
- Transmission Control Protocol. *See* TCP
- triangle assembler 283
- truncate() method 333
- typeMismatch attribute 318

U

- UFOs in SVG Aliens game
 - animating 229
 - creating big UFO 217–218
 - dynamic movement of 230–231
 - flocks of 227
 - making UFOs shoot 232
 - paths for 228
- UI (user interface) 378
- update_xy() function 417
- update() method 215, 231–232, 298, 328
- updateBrowserFilesList() function 88–89, 91
- updateready event 160, 162, 318
- upgradedNeeded event 145
- user input 294
- user interface. *See* UI

V

- valid attribute 318
- validateForm() function 68
- validating data 125

- validating forms
 - bypassing to save form details 51
 - custom validation 59–60
 - detecting failure with invalid event 60–61
 - new features for 13
 - reference links for 425
 - styling invalid elements 61–62
- validationMessage attribute 318
- validity attribute 318
- value property 54
- valueAsDate property 54
- valueAsNumber property 38, 53–55
- valueMissing attribute 318
- Vector Markup Language. *See* VML
- vertex shader 283
- Vibration API 417–418
- video
 - adjusting opacity of 260
 - API overview 21–22, 313
 - browser compatibility 239
 - converting between formats 252
 - custom controls for 255–256
 - encoding with FFmpeg tool
 - to MP4/h264 with AAC 387–388
 - to MP4/h264 with MP3 388
 - to Ogg/Theora 389
 - to WebM/VP8 388–389
 - Firefox browser 248
 - grayscale 261–262
 - Media Element interface
 - events in 245–246
 - overview 244
 - properties of 245
 - multiple formats with <source> element
 - discovering which video is playing 249–251
 - for browser compatibility 247–248
 - Opera browser 248
 - prerequisites for 239–240
 - reference links for 427
 - telestrator jukebox application
 - adding <canvas> element 253–254
 - adding clear button 264
 - adding frame around video 257–260
 - adjusting video opacity 260
 - capturing mouse movement 263
 - custom playback controls 255–256
 - determining state of media resources 245
 - displaying captured path over video 263
 - grayscale video 261–262
 - layout for 240–241
 - loading list of videos 243
 - overview 238–240
 - playing video on canplaythrough event 246
 - starting video when selected 244

- video (*continued*)
 - switching between videos 244
 - using event handlers to change video 245
 - <video> element 22, 241–242, 396, 399
 - viewBox property 203, 211–212, 230
 - views
 - controlling visibility of using CSS 137
 - creating with <section> elements 136
 - navigating between using JavaScript 137–139
 - VML (Vector Markup Language) 213
 - volume attribute 326
- W**
-
- W3C (World Wide Web Consortium) 311–312
 - WAI (Web Accessibility Initiative) 9
 - watchPosition() method 326
 - Web Hypertext Application Technology Working Group. *See* WHATWG
 - Web Messaging API 314
 - Web Socket API 314
 - Web Storage API
 - deleting data from localStorage 141–143
 - overview 26–27
 - reading data from localStorage 140–141
 - reference for 323
 - saving data to localStorage 141
 - WebGL (Web Graphics Library)
 - 3D drawing basics 297–298
 - building engine for
 - base engine logic 277
 - browser support for example 270–271
 - entity helper methods 280–281
 - entity storage 278
 - index.html 271–272
 - overview 269–270
 - requestAnimationFrame() function 275
 - shape entities with 3D data 279
 - Simple JavaScript Inheritance script 275
 - style.css 273
 - sylvester.js 276
 - time-saving scripts for 274–275
 - webgl_util.js 276
 - complex 3D models 301
 - creating buffers 287–288
 - displaying shape data on screen
 - adding matrix helpers 291
 - adding rotation logic 291
 - binding and drawing shapes 289
 - collision detection 290
 - using matrices and buffers 288
 - Geometry Destroyer game
 - 3D cube particle 305
 - 3D Polygon enemy 300
 - animating player entity 298
 - capturing user input 294
 - collision detection for enemies 303
 - creating enemies 304–305
 - creating player entity 296
 - customizing cubes 306–307
 - generating random enemy properties 302
 - HUD 295
 - player bullets 299–300
 - square particles 308
 - graphics cards 283–284
 - overview 32, 315
 - reference links for 427
 - shaders for 3D data
 - creating via OpenGL ES 284
 - pulling shader data from DOM 285–286
 - webgl_util.js file 276
 - WebM/VP8 encoding 388–389
 - WebRTC specification 394
 - WebSocket API
 - agile planning board example
 - building process for 114–115
 - business logic for 119–123
 - handling updates in browser 123
 - handling updates on server 124–125
 - overview 113–114
 - prerequisites for 114
 - template page 118–119
 - creating with Node.js 115–117
 - overview 25
 - vs. WebSocket protocol 360–361
 - WebSocket protocol
 - browser support for 362–363
 - overview 361–362
 - vs. WebSocket API 360–361
 - WebSocket-Node module 115, 117
 - websocket-sample.js file 117
 - WebVTT (Web Video Text Tracks) file
 - format 396
 - Welcome screen 193–194
 - WHATWG (Web Hypertext Application Technology Working Group) 19, 311–312
 - width attribute 242
 - willValidate attribute 318
 - Wilson smiley example 201–202
 - wilson.svg file 201
 - window event 185
 - window.location.reload() method 160
 - Windows 7
 - MySQL
 - creating databases 343–346
 - downloading 340–341
 - installing 341–343
 - running scripts 343–346

Windows 7 (*continued*)

PHP

- configuring Windows 7 IIS 336–337
- confirming installation 339
- downloading 337
- installing 338–339

World Wide Web Consortium. *See* W3C

- write() method 70, 333
- writend event 333
- writestart event 333
- ws.onmessage 123

X

- XHR (XML HTTP Request) object 4, 314
- XLink 209
- XMPP (eXtensible Messaging and Presence Protocol) 360

Y

- yieldForStorageUpdates() method 324